

# CJV200 Series



Eco-Solvent roll-based print & cut device

32"

54"

64"

## Total sign printing package

High value in a small footprint, the CJV200 provides indoor and outdoor durable printing with an integrated cutter and easy-to-use software for the perfect stand-alone bundle.

- Easily produce indoor and outdoor prints on a large selection of media with 'one printer to do it all' versatility in a small footprint.
- Enjoy outstanding quality and productivity, plus the industry's best outdoor durability at an attractive price point.
- Print a wide range of applications using this complete system with print & cut device, software, and a range of inks.
- Easy to use with paired RIP software for extreme accuracy when creating instant decals and large wall graphics.
- Outstanding quality and productivity at an attractive price point.
- Mimaki Core Technologies deliver exceptional results, economically, and with maximum productivity.
- Select from three model widths to suit your production needs.

*For best results, always use Mimaki original inks.*

# Mimaki® CJV200 Series

<b>Printhead</b>	On-demand piezo print head (single)		
<b>Print resolution</b>	X: 600,1200 dpi   Y: 600,900,1200 dpi		
<b>Print speed (4 color mode)</b>	183 sqft/hr (17 sqm/hr)		
	<b>CJV200-75</b>	<b>CJV200-130</b>	<b>CJV200-160</b>
<b>Maximum print width</b>	31.5 in (800 mm)	53.6 in (1361 mm)	63.4 in (1610 mm)
<b>Maximum media width</b>	31.9 in (810 mm)	53.9 in (1371 mm)	63.8 in (1620 mm)
<b>Weight (uncrated)</b>	231.4 lbs. (105 kg)	286.6 lbs. (130 kg)	308.6 lbs. (140 kg)
<b>Ink Type/Color</b>	Eco-Solvent inks		
	SS22 (C, M, Y, K, Lc, Lm, Lk, Or)		
<b>Ink Package Size</b>	440ml Cartridges		
	1L Bulk Ink Package (for use with optional Mimaki Bulk Ink System)		
<b>Media Thickness</b>	up to 0.04 in (1 mm)		
<b>Rolled Media Weight</b>	55 lbs. (25 kg)		
<b>Certifications</b>	VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star, RCM, EAC, KC, UKCA		
<b>Interface</b>	USB 2.0 Hi-speed   Ethernet 1000 BASE-T		
<b>Power Supply</b>	AC (100-120V / 200-240V±10%) × two 50/60Hz±1Hz		
<b>Power Consumption</b>	Max. 1320W x2   Sleep mode: 4.5W		
<b>Operational Environment</b>	Temperature: 68–86 °F ( 20–30 °C)		
	Humidity: 35–65%		
<b>Dimensions (W x D x H)</b>	CJV200-75: 77 in W x 29.5 in D x 54 in H (1960 mm W × 748 mm D × 1370 mm H)		
	CJV200-130: 99 in W x 29.5 in D x 54 in H (2520 mm W × 748 mm D × 1370 mm H)		
	CJV200-160: 109 in W x 29.5 in D x 54 in H (2770 mm W × 748 mm D × 1370 mm H)		
<b>Options</b>	Mimaki Bulk Ink System, NCU OPT, MBIS BKT OPT, 45kg Media Support		

Eco-Solvent roll-based print & cut device

32"

54"

64"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2024, Mimaki USA, Inc.

Rev. 8/25/24